

# Image and Kernel, Rank and Nullity

# Image and Kernel

## **Definitions.**

## **Definitions.**

Let  $T: \mathbb{V} \rightarrow \mathbb{W}$  be linear and let  $A$  be a matrix for  $T$

## **Definitions.**

Let  $T: \mathbb{V} \rightarrow \mathbb{W}$  be linear and let  $A$  be a matrix for  $T$  (so  $T(\mathbf{x}) = A \cdot \mathbf{x}$ ).

## **Definitions.**

Let  $T: \mathbb{V} \rightarrow \mathbb{W}$  be linear and let  $A$  be a matrix for  $T$  (so  $T(\mathbf{x}) = A \cdot \mathbf{x}$ ).

$$\text{im}(T) = \{\mathbf{b} \in \mathbb{W} \mid (\exists \mathbf{x})(T(\mathbf{x}) = \mathbf{b})\}$$

## Definitions.

Let  $T: \mathbb{V} \rightarrow \mathbb{W}$  be linear and let  $A$  be a matrix for  $T$  (so  $T(\mathbf{x}) = A \cdot \mathbf{x}$ ).

$$\begin{aligned}\text{im}(T) &= \{\mathbf{b} \in \mathbb{W} \mid (\exists \mathbf{x})(T(\mathbf{x}) = \mathbf{b})\} \\ &= \{\mathbf{b} \in \mathbb{W} \mid (\exists \mathbf{x})(A\mathbf{x} = \mathbf{b})\}\end{aligned}$$

## Definitions.

Let  $T: \mathbb{V} \rightarrow \mathbb{W}$  be linear and let  $A$  be a matrix for  $T$  (so  $T(\mathbf{x}) = A \cdot \mathbf{x}$ ).

$$\begin{aligned}\text{im}(T) &= \{\mathbf{b} \in \mathbb{W} \mid (\exists \mathbf{x})(T(\mathbf{x}) = \mathbf{b})\} \\ &= \{\mathbf{b} \in \mathbb{W} \mid (\exists \mathbf{x})(A\mathbf{x} = \mathbf{b})\} \\ &= \text{column space of } A\end{aligned}$$



## Definitions.

Let  $T: \mathbb{V} \rightarrow \mathbb{W}$  be linear and let  $A$  be a matrix for  $T$  (so  $T(\mathbf{x}) = A \cdot \mathbf{x}$ ).

$$\begin{aligned}\text{im}(T) &= \{\mathbf{b} \in \mathbb{W} \mid (\exists \mathbf{x})(T(\mathbf{x}) = \mathbf{b})\} \\ &= \{\mathbf{b} \in \mathbb{W} \mid (\exists \mathbf{x})(A\mathbf{x} = \mathbf{b})\} \\ &= \text{column space of } A \\ &= \text{a subspace of } \mathbb{W}\end{aligned}$$

## Definitions.

Let  $T: \mathbb{V} \rightarrow \mathbb{W}$  be linear and let  $A$  be a matrix for  $T$  (so  $T(\mathbf{x}) = A \cdot \mathbf{x}$ ).

$$\begin{aligned}\text{im}(T) &= \{\mathbf{b} \in \mathbb{W} \mid (\exists \mathbf{x})(T(\mathbf{x}) = \mathbf{b})\} \\ &= \{\mathbf{b} \in \mathbb{W} \mid (\exists \mathbf{x})(A\mathbf{x} = \mathbf{b})\} \\ &= \textbf{column space of } A \\ &= \text{a subspace of } \mathbb{W}\end{aligned}$$

$$\dim(\text{im}(T)) = \textbf{rank of } T = \textbf{rank}(A).$$

## Definitions.

Let  $T: \mathbb{V} \rightarrow \mathbb{W}$  be linear and let  $A$  be a matrix for  $T$  (so  $T(\mathbf{x}) = A \cdot \mathbf{x}$ ).

$$\begin{aligned}\text{im}(T) &= \{\mathbf{b} \in \mathbb{W} \mid (\exists \mathbf{x})(T(\mathbf{x}) = \mathbf{b})\} \\ &= \{\mathbf{b} \in \mathbb{W} \mid (\exists \mathbf{x})(A\mathbf{x} = \mathbf{b})\} \\ &= \textbf{column space of } A \\ &= \text{a subspace of } \mathbb{W}\end{aligned}$$

$\dim(\text{im}(T)) = \textbf{rank of } T = \textbf{rank}(A).$

$$\ker(T) = \{\mathbf{x} \in \mathbb{V} \mid T(\mathbf{x}) = \mathbf{0}\}$$

## Definitions.

Let  $T: \mathbb{V} \rightarrow \mathbb{W}$  be linear and let  $A$  be a matrix for  $T$  (so  $T(\mathbf{x}) = A \cdot \mathbf{x}$ ).

$$\begin{aligned}\text{im}(T) &= \{\mathbf{b} \in \mathbb{W} \mid (\exists \mathbf{x})(T(\mathbf{x}) = \mathbf{b})\} \\ &= \{\mathbf{b} \in \mathbb{W} \mid (\exists \mathbf{x})(A\mathbf{x} = \mathbf{b})\} \\ &= \textbf{column space of } A \\ &= \text{a subspace of } \mathbb{W}\end{aligned}$$

$\dim(\text{im}(T)) = \textbf{rank of } T = \textbf{rank}(A).$

$$\begin{aligned}\ker(T) &= \{\mathbf{x} \in \mathbb{V} \mid T(\mathbf{x}) = \mathbf{0}\} \\ &= \{\mathbf{x} \in \mathbb{V} \mid A\mathbf{x} = \mathbf{0}\}\end{aligned}$$

## Definitions.

Let  $T: \mathbb{V} \rightarrow \mathbb{W}$  be linear and let  $A$  be a matrix for  $T$  (so  $T(\mathbf{x}) = A \cdot \mathbf{x}$ ).

$$\begin{aligned}\text{im}(T) &= \{\mathbf{b} \in \mathbb{W} \mid (\exists \mathbf{x})(T(\mathbf{x}) = \mathbf{b})\} \\ &= \{\mathbf{b} \in \mathbb{W} \mid (\exists \mathbf{x})(A\mathbf{x} = \mathbf{b})\} \\ &= \textbf{column space of } A \\ &= \text{a subspace of } \mathbb{W}\end{aligned}$$

$\dim(\text{im}(T)) = \textbf{rank of } T = \textbf{rank}(A).$

$$\begin{aligned}\ker(T) &= \{\mathbf{x} \in \mathbb{V} \mid T(\mathbf{x}) = \mathbf{0}\} \\ &= \{\mathbf{x} \in \mathbb{V} \mid A\mathbf{x} = \mathbf{0}\} \\ &= \textbf{null space of } A\end{aligned}$$

## Definitions.

Let  $T: \mathbb{V} \rightarrow \mathbb{W}$  be linear and let  $A$  be a matrix for  $T$  (so  $T(\mathbf{x}) = A \cdot \mathbf{x}$ ).

$$\begin{aligned}\text{im}(T) &= \{\mathbf{b} \in \mathbb{W} \mid (\exists \mathbf{x})(T(\mathbf{x}) = \mathbf{b})\} \\ &= \{\mathbf{b} \in \mathbb{W} \mid (\exists \mathbf{x})(A\mathbf{x} = \mathbf{b})\} \\ &= \textbf{column space of } A \\ &= \text{a subspace of } \mathbb{W}\end{aligned}$$

$\dim(\text{im}(T)) = \textbf{rank of } T = \textbf{rank}(A).$

$$\begin{aligned}\ker(T) &= \{\mathbf{x} \in \mathbb{V} \mid T(\mathbf{x}) = \mathbf{0}\} \\ &= \{\mathbf{x} \in \mathbb{V} \mid A\mathbf{x} = \mathbf{0}\} \\ &= \textbf{null space of } A \\ &= \text{a subspace of } \mathbb{V}\end{aligned}$$

## Definitions.

Let  $T: \mathbb{V} \rightarrow \mathbb{W}$  be linear and let  $A$  be a matrix for  $T$  (so  $T(\mathbf{x}) = A \cdot \mathbf{x}$ ).

$$\begin{aligned}\text{im}(T) &= \{\mathbf{b} \in \mathbb{W} \mid (\exists \mathbf{x})(T(\mathbf{x}) = \mathbf{b})\} \\ &= \{\mathbf{b} \in \mathbb{W} \mid (\exists \mathbf{x})(A\mathbf{x} = \mathbf{b})\} \\ &= \textbf{column space of } A \\ &= \text{a subspace of } \mathbb{W}\end{aligned}$$

$$\dim(\text{im}(T)) = \textbf{rank of } T = \textbf{rank}(A).$$

$$\begin{aligned}\ker(T) &= \{\mathbf{x} \in \mathbb{V} \mid T(\mathbf{x}) = \mathbf{0}\} \\ &= \{\mathbf{x} \in \mathbb{V} \mid A\mathbf{x} = \mathbf{0}\} \\ &= \textbf{null space of } A \\ &= \text{a subspace of } \mathbb{V}\end{aligned}$$

$$\dim(\ker(T)) = \textbf{nullity of } T = \textbf{nullity}(A).$$

## Definitions.

Let  $T: \mathbb{V} \rightarrow \mathbb{W}$  be linear and let  $A$  be a matrix for  $T$  (so  $T(\mathbf{x}) = A \cdot \mathbf{x}$ ).

$$\begin{aligned}\text{im}(T) &= \{\mathbf{b} \in \mathbb{W} \mid (\exists \mathbf{x})(T(\mathbf{x}) = \mathbf{b})\} \\ &= \{\mathbf{b} \in \mathbb{W} \mid (\exists \mathbf{x})(A\mathbf{x} = \mathbf{b})\} \\ &= \textbf{column space of } A \\ &= \text{a subspace of } \mathbb{W}\end{aligned}$$

$$\dim(\text{im}(T)) = \textbf{rank of } T = \textbf{rank}(A).$$

$$\begin{aligned}\ker(T) &= \{\mathbf{x} \in \mathbb{V} \mid T(\mathbf{x}) = \mathbf{0}\} \\ &= \{\mathbf{x} \in \mathbb{V} \mid A\mathbf{x} = \mathbf{0}\} \\ &= \textbf{null space of } A \\ &= \text{a subspace of } \mathbb{V}\end{aligned}$$

$$\dim(\ker(T)) = \textbf{nullity of } T = \textbf{nullity}(A).$$



# Algorithms to compute bases for image and kernel

# Algorithms to compute bases for image and kernel

Let  $T(\mathbf{x}) = A \cdot \mathbf{x}$ .

# Algorithms to compute bases for image and kernel

Let  $T(\mathbf{x}) = A \cdot \mathbf{x}$ .

**Algorithm 1.**

# Algorithms to compute bases for image and kernel

Let  $T(\mathbf{x}) = A \cdot \mathbf{x}$ .

## **Algorithm 1.**

If the RRE form of  $A$  has pivots in columns  $i_1, \dots, i_r$ , then the corresponding columns of  $A$  form a basis for  $\text{col}(A) = \text{im}(T)$ .

# Algorithms to compute bases for image and kernel

Let  $T(\mathbf{x}) = A \cdot \mathbf{x}$ .

## **Algorithm 1.**

If the RRE form of  $A$  has pivots in columns  $i_1, \dots, i_r$ , then the corresponding columns of  $A$  form a basis for  $\text{col}(A) = \text{im}(T)$ . Hence  $\text{rank}(A) = r$ .

# Algorithms to compute bases for image and kernel

Let  $T(\mathbf{x}) = A \cdot \mathbf{x}$ .

## **Algorithm 1.**

If the RRE form of  $A$  has pivots in columns  $i_1, \dots, i_r$ , then the corresponding columns of  $A$  form a basis for  $\text{col}(A) = \text{im}(T)$ . Hence  $\text{rank}(A) = r$ .

## **Algorithm 2.**

# Algorithms to compute bases for image and kernel

Let  $T(\mathbf{x}) = A \cdot \mathbf{x}$ .

## **Algorithm 1.**

If the RRE form of  $A$  has pivots in columns  $i_1, \dots, i_r$ , then the corresponding columns of  $A$  form a basis for  $\text{col}(A) = \text{im}(T)$ . Hence  $\text{rank}(A) = r$ .

## **Algorithm 2.**

If the solution set to  $A\mathbf{x} = \mathbf{0}$  has the form  $x_{j_1} \mathbf{v}_{j_1} + \dots + x_{j_s} \mathbf{v}_{j_s}$ ,

# Algorithms to compute bases for image and kernel

Let  $T(\mathbf{x}) = A \cdot \mathbf{x}$ .

## Algorithm 1.

If the RRE form of  $A$  has pivots in columns  $i_1, \dots, i_r$ , then the corresponding columns of  $A$  form a basis for  $\text{col}(A) = \text{im}(T)$ . Hence  $\text{rank}(A) = r$ .

## Algorithm 2.

If the solution set to  $A\mathbf{x} = \mathbf{0}$  has the form  $x_{j_1} \mathbf{v}_{j_1} + \dots + x_{j_s} \mathbf{v}_{j_s}$ , where  $x_{j_1}, \dots, x_{j_s}$  are the free variables of the homogeneous system,



# Algorithms to compute bases for image and kernel

Let  $T(\mathbf{x}) = A \cdot \mathbf{x}$ .

## Algorithm 1.

If the RRE form of  $A$  has pivots in columns  $i_1, \dots, i_r$ , then the corresponding columns of  $A$  form a basis for  $\text{col}(A) = \text{im}(T)$ . Hence  $\text{rank}(A) = r$ .

## Algorithm 2.

If the solution set to  $A\mathbf{x} = \mathbf{0}$  has the form  $x_{j_1} \mathbf{v}_{j_1} + \dots + x_{j_s} \mathbf{v}_{j_s}$ , where  $x_{j_1}, \dots, x_{j_s}$  are the free variables of the homogeneous system, then  $\{\mathbf{v}_{j_1}, \dots, \mathbf{v}_{j_s}\}$  is a basis for  $\text{null}(A) = \ker(T)$ .

# Algorithms to compute bases for image and kernel

Let  $T(\mathbf{x}) = A \cdot \mathbf{x}$ .

## Algorithm 1.

If the RRE form of  $A$  has pivots in columns  $i_1, \dots, i_r$ , then the corresponding columns of  $A$  form a basis for  $\text{col}(A) = \text{im}(T)$ . Hence  $\text{rank}(A) = r$ .

## Algorithm 2.

If the solution set to  $A\mathbf{x} = \mathbf{0}$  has the form  $x_{j_1} \mathbf{v}_{j_1} + \dots + x_{j_s} \mathbf{v}_{j_s}$ , where  $x_{j_1}, \dots, x_{j_s}$  are the free variables of the homogeneous system, then  $\{\mathbf{v}_{j_1}, \dots, \mathbf{v}_{j_s}\}$  is a basis for  $\text{null}(A) = \ker(T)$ . Hence  $\text{nullity}(A) = s$ .

# Algorithms to compute bases for image and kernel

Let  $T(\mathbf{x}) = A \cdot \mathbf{x}$ .

## Algorithm 1.

If the RRE form of  $A$  has pivots in columns  $i_1, \dots, i_r$ , then the corresponding columns of  $A$  form a basis for  $\text{col}(A) = \text{im}(T)$ . Hence  $\text{rank}(A) = r$ .

## Algorithm 2.

If the solution set to  $A\mathbf{x} = \mathbf{0}$  has the form  $x_{j_1}\mathbf{v}_{j_1} + \dots + x_{j_s}\mathbf{v}_{j_s}$ , where  $x_{j_1}, \dots, x_{j_s}$  are the free variables of the homogeneous system, then  $\{\mathbf{v}_{j_1}, \dots, \mathbf{v}_{j_s}\}$  is a basis for  $\text{null}(A) = \ker(T)$ . Hence  $\text{nullity}(A) = s$ .

Observe:

# Algorithms to compute bases for image and kernel

Let  $T(\mathbf{x}) = A \cdot \mathbf{x}$ .

## Algorithm 1.

If the RRE form of  $A$  has pivots in columns  $i_1, \dots, i_r$ , then the corresponding columns of  $A$  form a basis for  $\text{col}(A) = \text{im}(T)$ . Hence  $\text{rank}(A) = r$ .

## Algorithm 2.

If the solution set to  $A\mathbf{x} = \mathbf{0}$  has the form  $x_{j_1} \mathbf{v}_{j_1} + \dots + x_{j_s} \mathbf{v}_{j_s}$ , where  $x_{j_1}, \dots, x_{j_s}$  are the free variables of the homogeneous system, then  $\{\mathbf{v}_{j_1}, \dots, \mathbf{v}_{j_s}\}$  is a basis for  $\text{null}(A) = \ker(T)$ . Hence  $\text{nullity}(A) = s$ .

Observe:

**Rank + Nullity Thm.**

# Algorithms to compute bases for image and kernel

Let  $T(\mathbf{x}) = A \cdot \mathbf{x}$ .

## Algorithm 1.

If the RRE form of  $A$  has pivots in columns  $i_1, \dots, i_r$ , then the corresponding columns of  $A$  form a basis for  $\text{col}(A) = \text{im}(T)$ . Hence  $\text{rank}(A) = r$ .

## Algorithm 2.

If the solution set to  $A\mathbf{x} = \mathbf{0}$  has the form  $x_{j_1}\mathbf{v}_{j_1} + \dots + x_{j_s}\mathbf{v}_{j_s}$ , where  $x_{j_1}, \dots, x_{j_s}$  are the free variables of the homogeneous system, then  $\{\mathbf{v}_{j_1}, \dots, \mathbf{v}_{j_s}\}$  is a basis for  $\text{null}(A) = \ker(T)$ . Hence  $\text{nullity}(A) = s$ .

Observe:

**Rank + Nullity Thm.**  $\text{rank}(A) + \text{nullity}(A) = \dim(\mathbb{V})$ .

# Algorithms to compute bases for image and kernel

Let  $T(\mathbf{x}) = A \cdot \mathbf{x}$ .

## Algorithm 1.

If the RRE form of  $A$  has pivots in columns  $i_1, \dots, i_r$ , then the corresponding columns of  $A$  form a basis for  $\text{col}(A) = \text{im}(T)$ . Hence  $\text{rank}(A) = r$ .

## Algorithm 2.

If the solution set to  $A\mathbf{x} = \mathbf{0}$  has the form  $x_{j_1}\mathbf{v}_{j_1} + \dots + x_{j_s}\mathbf{v}_{j_s}$ , where  $x_{j_1}, \dots, x_{j_s}$  are the free variables of the homogeneous system, then  $\{\mathbf{v}_{j_1}, \dots, \mathbf{v}_{j_s}\}$  is a basis for  $\text{null}(A) = \ker(T)$ . Hence  $\text{nullity}(A) = s$ .

Observe:

**Rank + Nullity Thm.**  $\text{rank}(A) + \text{nullity}(A) = \dim(\mathbb{V})$ .

*Proof.*

# Algorithms to compute bases for image and kernel

Let  $T(\mathbf{x}) = A \cdot \mathbf{x}$ .

## Algorithm 1.

If the RRE form of  $A$  has pivots in columns  $i_1, \dots, i_r$ , then the corresponding columns of  $A$  form a basis for  $\text{col}(A) = \text{im}(T)$ . Hence  $\text{rank}(A) = r$ .

## Algorithm 2.

If the solution set to  $A\mathbf{x} = \mathbf{0}$  has the form  $x_{j_1}\mathbf{v}_{j_1} + \dots + x_{j_s}\mathbf{v}_{j_s}$ , where  $x_{j_1}, \dots, x_{j_s}$  are the free variables of the homogeneous system, then  $\{\mathbf{v}_{j_1}, \dots, \mathbf{v}_{j_s}\}$  is a basis for  $\text{null}(A) = \ker(T)$ . Hence  $\text{nullity}(A) = s$ .

Observe:

**Rank + Nullity Thm.**  $\text{rank}(A) + \text{nullity}(A) = \dim(\mathbb{V})$ .

*Proof.*

$$\text{rank}(A) + \text{nullity}(A) = \text{number of pivot cols.} + \text{number of non-pivot cols.}$$

# Algorithms to compute bases for image and kernel

Let  $T(\mathbf{x}) = A \cdot \mathbf{x}$ .

## Algorithm 1.

If the RRE form of  $A$  has pivots in columns  $i_1, \dots, i_r$ , then the corresponding columns of  $A$  form a basis for  $\text{col}(A) = \text{im}(T)$ . Hence  $\text{rank}(A) = r$ .

## Algorithm 2.

If the solution set to  $A\mathbf{x} = \mathbf{0}$  has the form  $x_{j_1}\mathbf{v}_{j_1} + \dots + x_{j_s}\mathbf{v}_{j_s}$ , where  $x_{j_1}, \dots, x_{j_s}$  are the free variables of the homogeneous system, then  $\{\mathbf{v}_{j_1}, \dots, \mathbf{v}_{j_s}\}$  is a basis for  $\text{null}(A) = \ker(T)$ . Hence  $\text{nullity}(A) = s$ .

Observe:

**Rank + Nullity Thm.**  $\text{rank}(A) + \text{nullity}(A) = \dim(\mathbb{V})$ .

*Proof.*

$$\begin{aligned}\text{rank}(A) + \text{nullity}(A) &= \text{number of pivot cols.} + \text{number of non-pivot cols.} \\ &= \text{number of columns of } A\end{aligned}$$



# Algorithms to compute bases for image and kernel

Let  $T(\mathbf{x}) = A \cdot \mathbf{x}$ .

## Algorithm 1.

If the RRE form of  $A$  has pivots in columns  $i_1, \dots, i_r$ , then the corresponding columns of  $A$  form a basis for  $\text{col}(A) = \text{im}(T)$ . Hence  $\text{rank}(A) = r$ .

## Algorithm 2.

If the solution set to  $A\mathbf{x} = \mathbf{0}$  has the form  $x_{j_1}\mathbf{v}_{j_1} + \dots + x_{j_s}\mathbf{v}_{j_s}$ , where  $x_{j_1}, \dots, x_{j_s}$  are the free variables of the homogeneous system, then  $\{\mathbf{v}_{j_1}, \dots, \mathbf{v}_{j_s}\}$  is a basis for  $\text{null}(A) = \ker(T)$ . Hence  $\text{nullity}(A) = s$ .

Observe:

**Rank + Nullity Thm.**  $\text{rank}(A) + \text{nullity}(A) = \dim(\mathbb{V})$ .

*Proof.*

$$\begin{aligned}\text{rank}(A) + \text{nullity}(A) &= \text{number of pivot cols.} + \text{number of non-pivot cols.} \\ &= \text{number of columns of } A \\ &= \dim(\mathbb{V}).\end{aligned}$$

# Algorithms to compute bases for image and kernel

Let  $T(\mathbf{x}) = A \cdot \mathbf{x}$ .

## Algorithm 1.

If the RRE form of  $A$  has pivots in columns  $i_1, \dots, i_r$ , then the corresponding columns of  $A$  form a basis for  $\text{col}(A) = \text{im}(T)$ . Hence  $\text{rank}(A) = r$ .

## Algorithm 2.

If the solution set to  $A\mathbf{x} = \mathbf{0}$  has the form  $x_{j_1}\mathbf{v}_{j_1} + \dots + x_{j_s}\mathbf{v}_{j_s}$ , where  $x_{j_1}, \dots, x_{j_s}$  are the free variables of the homogeneous system, then  $\{\mathbf{v}_{j_1}, \dots, \mathbf{v}_{j_s}\}$  is a basis for  $\text{null}(A) = \ker(T)$ . Hence  $\text{nullity}(A) = s$ .

Observe:

**Rank + Nullity Thm.**  $\text{rank}(A) + \text{nullity}(A) = \dim(\mathbb{V})$ .

*Proof.*

$$\begin{aligned}\text{rank}(A) + \text{nullity}(A) &= \text{number of pivot cols.} + \text{number of non-pivot cols.} \\ &= \text{number of columns of } A \\ &= \dim(\mathbb{V}). \square\end{aligned}$$

# Example

## Example

Define  $T: \mathbb{R}^2 \rightarrow \mathbb{R}^2$  by  $T(\mathbf{x}) = A \cdot \mathbf{x} = \begin{bmatrix} 1 & 2 \\ 1 & 2 \end{bmatrix} \cdot \begin{bmatrix} x_1 \\ x_2 \end{bmatrix}$ .

# Example

Define  $T: \mathbb{R}^2 \rightarrow \mathbb{R}^2$  by  $T(\mathbf{x}) = A \cdot \mathbf{x} = \begin{bmatrix} 1 & 2 \\ 1 & 2 \end{bmatrix} \cdot \begin{bmatrix} x_1 \\ x_2 \end{bmatrix}$ .

**Algorithm 1.**

# Example

Define  $T: \mathbb{R}^2 \rightarrow \mathbb{R}^2$  by  $T(\mathbf{x}) = A \cdot \mathbf{x} = \begin{bmatrix} 1 & 2 \\ 1 & 2 \end{bmatrix} \cdot \begin{bmatrix} x_1 \\ x_2 \end{bmatrix}$ .

**Algorithm 1.** ( $\text{im}(T)$  or  $\text{col}(A)$ )

# Example

Define  $T: \mathbb{R}^2 \rightarrow \mathbb{R}^2$  by  $T(\mathbf{x}) = A \cdot \mathbf{x} = \begin{bmatrix} 1 & 2 \\ 1 & 2 \end{bmatrix} \cdot \begin{bmatrix} x_1 \\ x_2 \end{bmatrix}$ .

**Algorithm 1.** ( $\text{im}(T)$  or  $\text{col}(A)$ )

RRE form of  $A$ ?

# Example

Define  $T: \mathbb{R}^2 \rightarrow \mathbb{R}^2$  by  $T(\mathbf{x}) = A \cdot \mathbf{x} = \begin{bmatrix} 1 & 2 \\ 1 & 2 \end{bmatrix} \cdot \begin{bmatrix} x_1 \\ x_2 \end{bmatrix}$ .

**Algorithm 1.** ( $\text{im}(T)$  or  $\text{col}(A)$ )

RRE form of  $A$ ?

$$\begin{bmatrix} 1 & 2 \\ 1 & 2 \end{bmatrix} \xrightarrow{-R_1 + R_2} \begin{bmatrix} 1 & 2 \\ 0 & 0 \end{bmatrix}$$



# Example

Define  $T: \mathbb{R}^2 \rightarrow \mathbb{R}^2$  by  $T(\mathbf{x}) = A \cdot \mathbf{x} = \begin{bmatrix} 1 & 2 \\ 1 & 2 \end{bmatrix} \cdot \begin{bmatrix} x_1 \\ x_2 \end{bmatrix}$ .

**Algorithm 1.** ( $\text{im}(T)$  or  $\text{col}(A)$ )

RRE form of  $A$ ?

$$\begin{bmatrix} 1 & 2 \\ 1 & 2 \end{bmatrix} \xrightarrow{-R_1 + R_2} \begin{bmatrix} 1 & 2 \\ 0 & 0 \end{bmatrix} \quad (\text{Done!})$$

# Example

Define  $T: \mathbb{R}^2 \rightarrow \mathbb{R}^2$  by  $T(\mathbf{x}) = A \cdot \mathbf{x} = \begin{bmatrix} 1 & 2 \\ 1 & 2 \end{bmatrix} \cdot \begin{bmatrix} x_1 \\ x_2 \end{bmatrix}$ .

**Algorithm 1.** ( $\text{im}(T)$  or  $\text{col}(A)$ )

RRE form of  $A$ ?

$$\begin{bmatrix} 1 & 2 \\ 1 & 2 \end{bmatrix} \xrightarrow{-R_1 + R_2} \begin{bmatrix} 1 & 2 \\ 0 & 0 \end{bmatrix} \quad (\text{Done!})$$

First column of RRE form is the only pivot column of  $A$ , so  $\left( \begin{bmatrix} 1 \\ 1 \end{bmatrix} \right)$  is an ordered basis for  $\text{im}(T)$

# Example

Define  $T: \mathbb{R}^2 \rightarrow \mathbb{R}^2$  by  $T(\mathbf{x}) = A \cdot \mathbf{x} = \begin{bmatrix} 1 & 2 \\ 1 & 2 \end{bmatrix} \cdot \begin{bmatrix} x_1 \\ x_2 \end{bmatrix}$ .

**Algorithm 1.** ( $\text{im}(T)$  or  $\text{col}(A)$ )

RRE form of  $A$ ?

$$\begin{bmatrix} 1 & 2 \\ 1 & 2 \end{bmatrix} \xrightarrow{-R_1 + R_2} \begin{bmatrix} 1 & 2 \\ 0 & 0 \end{bmatrix} \quad (\text{Done!})$$

First column of RRE form is the only pivot column of  $A$ , so  $\left( \begin{bmatrix} 1 \\ 1 \end{bmatrix} \right)$  is an ordered basis for  $\text{im}(T)$  ( $= \text{col}(A)$ ),

# Example

Define  $T: \mathbb{R}^2 \rightarrow \mathbb{R}^2$  by  $T(\mathbf{x}) = A \cdot \mathbf{x} = \begin{bmatrix} 1 & 2 \\ 1 & 2 \end{bmatrix} \cdot \begin{bmatrix} x_1 \\ x_2 \end{bmatrix}$ .

**Algorithm 1.** ( $\text{im}(T)$  or  $\text{col}(A)$ )

RRE form of  $A$ ?

$$\begin{bmatrix} 1 & 2 \\ 1 & 2 \end{bmatrix} \xrightarrow{-R_1 + R_2} \begin{bmatrix} 1 & 2 \\ 0 & 0 \end{bmatrix} \quad (\text{Done!})$$

First column of RRE form is the only pivot column of  $A$ , so  $\left( \begin{bmatrix} 1 \\ 1 \end{bmatrix} \right)$  is an ordered basis for  $\text{im}(T)$  ( $= \text{col}(A)$ ), and  $\text{rank}(T) = 1$ .

**Algorithm 2.**

# Example

Define  $T: \mathbb{R}^2 \rightarrow \mathbb{R}^2$  by  $T(\mathbf{x}) = A \cdot \mathbf{x} = \begin{bmatrix} 1 & 2 \\ 1 & 2 \end{bmatrix} \cdot \begin{bmatrix} x_1 \\ x_2 \end{bmatrix}$ .

**Algorithm 1.** ( $\text{im}(T)$  or  $\text{col}(A)$ )

RRE form of  $A$ ?

$$\begin{bmatrix} 1 & 2 \\ 1 & 2 \end{bmatrix} \xrightarrow{-R_1 + R_2} \begin{bmatrix} 1 & 2 \\ 0 & 0 \end{bmatrix} \quad (\text{Done!})$$

First column of RRE form is the only pivot column of  $A$ , so  $\left( \begin{bmatrix} 1 \\ 1 \end{bmatrix} \right)$  is an ordered basis for  $\text{im}(T)$  ( $= \text{col}(A)$ ), and  $\text{rank}(T) = 1$ .

**Algorithm 2.** ( $\text{ker}(T)$  or  $\text{null}(A)$ )

# Example

Define  $T: \mathbb{R}^2 \rightarrow \mathbb{R}^2$  by  $T(\mathbf{x}) = A \cdot \mathbf{x} = \begin{bmatrix} 1 & 2 \\ 1 & 2 \end{bmatrix} \cdot \begin{bmatrix} x_1 \\ x_2 \end{bmatrix}$ .

**Algorithm 1.** ( $\text{im}(T)$  or  $\text{col}(A)$ )

RRE form of  $A$ ?

$$\begin{bmatrix} 1 & 2 \\ 1 & 2 \end{bmatrix} \xrightarrow{-R_1 + R_2} \begin{bmatrix} 1 & 2 \\ 0 & 0 \end{bmatrix} \quad (\text{Done!})$$

First column of RRE form is the only pivot column of  $A$ , so  $\left( \begin{bmatrix} 1 \\ 1 \end{bmatrix} \right)$  is an ordered basis for  $\text{im}(T)$  ( $= \text{col}(A)$ ), and  $\text{rank}(T) = 1$ .

**Algorithm 2.** ( $\text{ker}(T)$  or  $\text{null}(A)$ )

From the computation in Algorithm 1,  $x_2$  is the only free variable,

# Example

Define  $T: \mathbb{R}^2 \rightarrow \mathbb{R}^2$  by  $T(\mathbf{x}) = A \cdot \mathbf{x} = \begin{bmatrix} 1 & 2 \\ 1 & 2 \end{bmatrix} \cdot \begin{bmatrix} x_1 \\ x_2 \end{bmatrix}$ .

**Algorithm 1.** ( $\text{im}(T)$  or  $\text{col}(A)$ )

RRE form of  $A$ ?

$$\begin{bmatrix} 1 & 2 \\ 1 & 2 \end{bmatrix} \xrightarrow{-R_1 + R_2} \begin{bmatrix} 1 & 2 \\ 0 & 0 \end{bmatrix} \quad (\text{Done!})$$

First column of RRE form is the only pivot column of  $A$ , so  $\left( \begin{bmatrix} 1 \\ 1 \end{bmatrix} \right)$  is an ordered basis for  $\text{im}(T)$  ( $= \text{col}(A)$ ), and  $\text{rank}(T) = 1$ .

**Algorithm 2.** ( $\text{ker}(T)$  or  $\text{null}(A)$ )

From the computation in Algorithm 1,  $x_2$  is the only free variable, and the solution to the homogeneous system is  $\begin{bmatrix} x_1 \\ x_2 \end{bmatrix} = \begin{bmatrix} -2x_2 \\ x_2 \end{bmatrix} = x_2 \begin{bmatrix} -2 \\ 1 \end{bmatrix}$ .

# Example

Define  $T: \mathbb{R}^2 \rightarrow \mathbb{R}^2$  by  $T(\mathbf{x}) = A \cdot \mathbf{x} = \begin{bmatrix} 1 & 2 \\ 1 & 2 \end{bmatrix} \cdot \begin{bmatrix} x_1 \\ x_2 \end{bmatrix}$ .

**Algorithm 1.** ( $\text{im}(T)$  or  $\text{col}(A)$ )

RRE form of  $A$ ?

$$\begin{bmatrix} 1 & 2 \\ 1 & 2 \end{bmatrix} \xrightarrow{-R_1+R_2} \begin{bmatrix} 1 & 2 \\ 0 & 0 \end{bmatrix} \quad (\text{Done!})$$

First column of RRE form is the only pivot column of  $A$ , so  $\left( \begin{bmatrix} 1 \\ 1 \end{bmatrix} \right)$  is an ordered basis for  $\text{im}(T)$  ( $= \text{col}(A)$ ), and  $\text{rank}(T) = 1$ .

**Algorithm 2.** ( $\text{ker}(T)$  or  $\text{null}(A)$ )

From the computation in Algorithm 1,  $x_2$  is the only free variable, and the solution to the homogeneous system is  $\begin{bmatrix} x_1 \\ x_2 \end{bmatrix} = \begin{bmatrix} -2x_2 \\ x_2 \end{bmatrix} = x_2 \begin{bmatrix} -2 \\ 1 \end{bmatrix}$ . Hence

$\left( \begin{bmatrix} -2 \\ 1 \end{bmatrix} \right)$  is an ordered basis for  $\text{ker}(T)$



# Example

Define  $T: \mathbb{R}^2 \rightarrow \mathbb{R}^2$  by  $T(\mathbf{x}) = A \cdot \mathbf{x} = \begin{bmatrix} 1 & 2 \\ 1 & 2 \end{bmatrix} \cdot \begin{bmatrix} x_1 \\ x_2 \end{bmatrix}$ .

**Algorithm 1.** ( $\text{im}(T)$  or  $\text{col}(A)$ )

RRE form of  $A$ ?

$$\begin{bmatrix} 1 & 2 \\ 1 & 2 \end{bmatrix} \xrightarrow{-R_1+R_2} \begin{bmatrix} 1 & 2 \\ 0 & 0 \end{bmatrix} \quad (\text{Done!})$$

First column of RRE form is the only pivot column of  $A$ , so  $\left(\begin{bmatrix} 1 \\ 1 \end{bmatrix}\right)$  is an ordered basis for  $\text{im}(T)$  ( $= \text{col}(A)$ ), and  $\text{rank}(T) = 1$ .

**Algorithm 2.** ( $\text{ker}(T)$  or  $\text{null}(A)$ )

From the computation in Algorithm 1,  $x_2$  is the only free variable, and the solution to the homogeneous system is  $\begin{bmatrix} x_1 \\ x_2 \end{bmatrix} = \begin{bmatrix} -2x_2 \\ x_2 \end{bmatrix} = x_2 \begin{bmatrix} -2 \\ 1 \end{bmatrix}$ . Hence

$\left(\begin{bmatrix} -2 \\ 1 \end{bmatrix}\right)$  is an ordered basis for  $\text{ker}(T)$  ( $= \text{null}(A)$ ),

# Example

Define  $T: \mathbb{R}^2 \rightarrow \mathbb{R}^2$  by  $T(\mathbf{x}) = A \cdot \mathbf{x} = \begin{bmatrix} 1 & 2 \\ 1 & 2 \end{bmatrix} \cdot \begin{bmatrix} x_1 \\ x_2 \end{bmatrix}$ .

**Algorithm 1.** ( $\text{im}(T)$  or  $\text{col}(A)$ )

RRE form of  $A$ ?

$$\begin{bmatrix} 1 & 2 \\ 1 & 2 \end{bmatrix} \xrightarrow{-R_1+R_2} \begin{bmatrix} 1 & 2 \\ 0 & 0 \end{bmatrix} \quad (\text{Done!})$$

First column of RRE form is the only pivot column of  $A$ , so  $\left( \begin{bmatrix} 1 \\ 1 \end{bmatrix} \right)$  is an ordered basis for  $\text{im}(T)$  ( $= \text{col}(A)$ ), and  $\text{rank}(T) = 1$ .

**Algorithm 2.** ( $\text{ker}(T)$  or  $\text{null}(A)$ )

From the computation in Algorithm 1,  $x_2$  is the only free variable, and the solution to the homogeneous system is  $\begin{bmatrix} x_1 \\ x_2 \end{bmatrix} = \begin{bmatrix} -2x_2 \\ x_2 \end{bmatrix} = x_2 \begin{bmatrix} -2 \\ 1 \end{bmatrix}$ . Hence

$\left( \begin{bmatrix} -2 \\ 1 \end{bmatrix} \right)$  is an ordered basis for  $\text{ker}(T)$  ( $= \text{null}(A)$ ), and  $\text{nullity}(T) = 1$ .

# Example

Define  $T: \mathbb{R}^2 \rightarrow \mathbb{R}^2$  by  $T(\mathbf{x}) = A \cdot \mathbf{x} = \begin{bmatrix} 1 & 2 \\ 1 & 2 \end{bmatrix} \cdot \begin{bmatrix} x_1 \\ x_2 \end{bmatrix}$ .

**Algorithm 1.** ( $\text{im}(T)$  or  $\text{col}(A)$ )

RRE form of  $A$ ?

$$\begin{bmatrix} 1 & 2 \\ 1 & 2 \end{bmatrix} \xrightarrow{-R_1+R_2} \begin{bmatrix} 1 & 2 \\ 0 & 0 \end{bmatrix} \quad (\text{Done!})$$

First column of RRE form is the only pivot column of  $A$ , so  $\left( \begin{bmatrix} 1 \\ 1 \end{bmatrix} \right)$  is an ordered basis for  $\text{im}(T)$  ( $= \text{col}(A)$ ), and  $\text{rank}(T) = 1$ .

**Algorithm 2.** ( $\ker(T)$  or  $\text{null}(A)$ )

From the computation in Algorithm 1,  $x_2$  is the only free variable, and the solution to the homogeneous system is  $\begin{bmatrix} x_1 \\ x_2 \end{bmatrix} = \begin{bmatrix} -2x_2 \\ x_2 \end{bmatrix} = x_2 \begin{bmatrix} -2 \\ 1 \end{bmatrix}$ . Hence

$\left( \begin{bmatrix} -2 \\ 1 \end{bmatrix} \right)$  is an ordered basis for  $\ker(T)$  ( $= \text{null}(A)$ ), and  $\text{nullity}(T) = 1$ .